

Vectec have supplied fuel tanks to the private & public sector for over 15 years.

The tank is an inner storage tank, externally encased within an outer weatherproof bund to ensure any leakage or nominal overfill situation is safely contained.

The tank is easily transportable as a one-piece unit and reduces costly and time consuming site work.

The tank is delivered to the customer's premises. If at a later date a new site is required it has only to be emptied of contents, cleaned internally, uplifted and transported to its new location.



## Advantages

- Enclosed banded tank.
- Easily transportable.
- Reduced maintenance costs.
- Space saving.
- Weatherproof.
- Sizes/capacity to suit most situations.
- Cuts costly site work.
- Finished in green or black oil resistant paint.
- Needs only suitable level hard standing (concrete ideal).
- Off loading and positioning facilities available if required.
- Over filled product can be recovered from enclosed bund.
- Clients own in-house colours can be accommodated on request.
- Compliant with control of pollution (Oil Storage) (England) regulations 2001 (PPG2).

Model	Capacity (Litres)	Dimensions approx			Weight approx
		L	W	H	
F 120	120,000	15100	3000	3200	22 ton
F 110	110,000	14100	3000	3200	21 ton
F 100	100,000	12500	3000	3200	19.5 ton
F 90	90,000	11600	3000	3200	18 ton
F 80	80,000	10300	3000	3200	17 ton
F 70	70,000	8700	3000	3200	15.5 ton
F 60	60,000	7500	3000	3200	12.5 ton
F 50	50,000	7000	3000	3200	12 ton
F 45	45,000	5900	3000	3200	11.5 ton
F 40	40,000	5000	3000	3200	11 ton
F 35	35,000	4500	3000	3200	10.5 ton
F 30	30,000	5650	2500	2500	8.5 ton
F 25	25,000	4700	2500	2500	7.5 ton
F 20	20,000	4000	2500	2500	6 ton

Lead times can vary depending on size, please contact [sales@vectec.co.uk](mailto:sales@vectec.co.uk) for further information

