

Air Operated Oil Pump - Heavy Duty/High Speed

- Faster flow rate than a normal 5:1 ratio oil pump.
- 5:1 ratio, ideal when you have long runs of pipework.
- Suitable with oils up to SAE 240.
- Supplied with a suction pipe for drums/tanks.
- Comes with a 2" M BSPP drum/tank adaptor.
- Regulate air inlet pressure 70 - 115psi (5 - 8 bar).
- Max pressure 115psi (8 bar).
- **Important:** Filter regulator & lubricator must be fitted or warranty void (see page 50).

HYTEK
Engineered Product

2 YEARS
WARRANTY
OIL



AOP.5HDC

Stk Code	Description	Ratio	Flow Rate	Inlet	Outlet	Air Inlet	Max Air Consumption	Suction
AOP.5HDC	Oil pump	5:1	25L/min	1" F BSPP	3/4" M BSPP	1/4" F BSPP	8 bar 180L/min	940mm pipe
AIR.FRC	Air regulator							

Air Operated Oil Pumps - 600 Series

- Comes with a 12 months parts warranty.
- Suitable with waste oils (SAE 80) & antifreeze.
- Stubby pump comes with a 2" M BSPP drum/tank adaptor.
- Regulate air inlet pressure 70 - 115psi (5 - 8 bar).
- Max pressure 115psi (8bar).
- **Important:** Filter regulator & lubricator must be fitted or warranty void (see page 50).
- **Option:** Suction pipes see page 46.

ECODORA

MADE IN ITALY
ANTIFREEZE
OIL



Optional:
suction pipe

AOP.1B

Stk Code	Description	Ratio	Flow Rate	Inlet	Outlet	Air Inlet	Max Air Consumption
AOP.1B	For oil/ antifreeze (600 series)	1:1	23L/min	1" F BSPP	1/2" F BSPP	1/4" F BSPP	8 bar 230L/min
AIR.FRC	Air regulator filter & lubricator	-	-	-	-	-	-

Air Oil Pump Accessories For Above

- For air operated oil pumps 600 series above.
- Wall mounting bracket (AOP.WALL1).
- For suction pipes use AOP.S90 or AOP.S60. See page 46.

ECODORA

MADE IN ITALY



AOP.WALL.1

Stk Code	Description
AOP.WALL.1	Wall mount bracket for AOP.1B (600 series)